

Wind Mitigation Discount

What Is A Wind Mitigation Discount? Who Qualifies for This Discount?	 This discount is extended to properties that have taken proactive measures to limit damage from high winds. Some homeowners will fortify their homes above and beyond the required building codes to prevent loss. The system will automatically evaluate all quoted homes for eligibility and apply a discount based on the roof age and year of construction. Agents should ask, on every quote, if an applicant has had a recent wind mitigation inspection.
	 If the applicant says no, defaulted values should not be modified. NOTE: Agent should never select "No" on the Wind Mitigation Credits question since every property has some defaulted credits.
Which Credits are Determined by a Wind Mitigation Inspection?	 Reinforced Concrete Roof Deck Roof Covering (Non-FBC or FBC) Roof Deck Attachment (Level A-6d-6"/12", Level B-8d-6"/12", Level C-8d-6"/6", Reinforced Concrete Roof Deck) Roof Wall Attachment Features (Toe Nails, Clips, Single Wraps, Double Wraps, Reinforced Concrete Roof Deck) Secondary Water Resistance (SWR) Opening Protection (Hurricane Impact, Basic Impact, None) Roof Shape (Hip, Gable, Flat, Other)
Wind Mitigation Inspection Documentation Requirements	 The inspection must be in the primary insured's name only; an inspection in a previous owner's name does not qualify. The inspection must be completed using the approved Uniform Mitigation Verification Inspection Form version 2012. The inspection must include the colored photos taken by the inspector. Document must be received within 30 days of the policy purchase date for New Business. Policyholders who fail to provide a copy of the inspection within 30 days will have any additional discounts removed, and the policy will be rated with defaults based on YOC and roof age. Documents received mid-term resulting in a premium change will be applied no earlier than the effective date of the current term or the date of the inspection, whichever is later.
How Do I Add Discounts to an Active Policy? How do I know what the default credits are?	 Request that the inspection be emailed to TRUE at memberservice@trueins.com (members) or agent-support@trueins.com (agents) and retrieve the document from Zendesk. Use the Wind Mitigation Inspection below to apply the correct credits. Use the Wind Mitigation Default Credit Chart below to determine the correct default credits.



Wind Mitigation Discount

Wind Mitigation Default Credit Chart

Wind Mitigation Default Credit Chart									
YOC	Roof Year	Roof Cover	Roof Deck	Roof to Wall	OP	SWR			
Pre-2002	Pre-2002	Non-FBC	Α	Toe Nail	No	No			
Pre-2002	2002+	FBC	С	Toe Nail	No	No			
2002+	2002+	FBC	С	Clips	No	No			
The below credits are specific to counties below with a 2012+ YOC									
2012+	2+ 2012+ FBC		С	Clips	Hurricane	Yes			
Brevard	Collier	Glades	Lee	Miami-Dade	Palm Beach	Sarasota			
Broward	Desoto	Hendry	Manatee	Monroe	Pinellas	St. Lucie			
Charlotte	Escambia	Indian River	Martin						
Notes: All Reinforced Concrete Decks, Single Wraps, and Double Wraps require a									
	Wind Mitigation Inspection be submitted								

	W	ind Mitigation I	Insp	e	ct	ion	Example
	Uniform Mitigation Verification Insp Maintain a copy of this form and any documentation provid					greater resi ! psf.	stance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least
Ī	Your all a Photo		RCR		D.	Reinforce	f Concrete Roof Deck.
t	Inspection Date: The Inspection Date and all Owner Information is re	quired	Refer		E.	Other:	
ł	Owner Name:	Contact Person:	Level /	4 🗆	F. 1	Unknown	or unidentified.
t	Address: This Address must match property address on the policy	Home Phone: Contact info is	Level /		G.	No attic ac	ocess,
t	City: Zip:	Work Phone: not required	- 4	Ro	anf to	Wall Arra	nchment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within
t	County:	Cell Phone:					or outside corner of the roof in determination of WEAKEST type)
t	Insurance Company:	Policy#:	Toe		Α.	Toe Nails	** /
ij	Year of Home: # of Stories:	Email:	Nails				Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to
1							the top plate of the wall, or
	NOTE: Any documentation used in validating the compliance or existence of each co						Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	accompany this form. At least one photograph must accompany this form to validate though 7. The insurer may ask additional questions regarding the mitigated feature			M	inima	l conditio	ns to qualify for categories B, C, or D. All visible metal connectors are:
				1411			Secured to truss/rafter with a minimum of three (3) nails, and
V/A	 Building Code: Was the structure built in compliance with the Florida Building Code the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-9 						Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from
							the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe
	A. Built in compliance with the FBC: Year Built, For homes built in: a date after 3/1/2002: Building Permit Application Date @@@date.com	2002/2003 provide a permit application with					corrosion.
	B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built		Clips		B.	Clips	
	provide a permit application with a date after 9/1/1994: Building Permit Application	on Date occuparying / /					Metal connectors that do not wrap over the top of the truss/rafter, or
	☐ C. Unknown or does not meet the requirements of Answer "A" or "B"						Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail
N/A	 Roof Covering: Select all roof covering types in use. Provide the permit application d. 	ate OR ERC/MDC Product Approval number					position requirements of C or D, but is secured with a minimum of 3 nails.
WA	OR Year of Original Installation/Replacement OR indicate that no information was aver	silable to verify compliance for each roof	Single		C.	Single Wra	aps
	covering identified.		Wraps				Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a
	Permit Application FBC or MDC	Year of Original Installation or Provided for	Double				minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
	2.1 Roof Covering Type: Date Product Approval 6	Replacement Compliance	Double		D.	Double W	
	1. Asphalt/Fiberglass Shingle / /		Wraps				Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond
	2. Concrete/Clay Tile						beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
	3. Metal / /						Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on
	4. Bulk Up						both sides, and is secured to the top plate with a minimum of three nails on each side.
	5. Montrons		Refer	П	E	Structural	Anchor bolts structurally connected or reinforced concrete roof.
	6. Other		Refer			Other:	
	6.0ter		Toe				or unidentified
FBC	 A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Prod 		Nails			No attic ac	
FBC	installation OR have a roofing permit application date on or after 3/1/02 OR the ro B. All roof coverings have a Miami-Dade Product Approval listing current at time		Ivalia		11.	No attic ac	4403
	roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is origin	nal and built in 1997 or later.	5				What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
	C. One or more roof coverings do not meet the requirements of Answer "A" or "B	".					
KOI III I	D. No roof coverings meet the requirements of Answer "A" or "B".		Hip	ш	A.	Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter.
	 Roof Deck Attachment: What is the weakest form of roof deck attachment? 		Flat	П	В	Flat Roof	Total length of non-hip features:feet; Total roof system perimeter:feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of
.eve	A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss				ь.	I lat Root	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft
	by staples or 6d nails spaced at 6" along the edge and 12" in the field. OR- Bat shingles. OR- Any system of screws, nails, adhesives, other deck fastening system	ten decking supporting wood shakes or wood	Gable		C.	Other Roo	
	mean uplift less than that required for Options B or C below.	n or truss/ratter spacing that has an equivalent	Other				
eve	B D B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached	to the roof truss/rafter (spaced a maximum of	. 6	Sec	cond	arv Water	Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR)
	24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.						called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the
	other deck fastening system or truss/rafter spacing that is shown to have an equi						or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the
	maximum of 12 inches in the field or has a mean uplift resistance of at least 103 p						rom water intrusion in the event of roof covering loss.
.eve	C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached		SWR - N		В.	No SWR.	
	24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. decking with a minimum of 2 nails per board (or 1 nail per board if each board is		OWK - N	<u>ч</u> П	C.	Unknown	or undetermined.
	Any system of screws, nails, adhesives, other deck fastening system or truss/rafte	r spacing that is shown to have an equivalent		nenec	ctors	Initials	Property Address Initials and Property Address are needed on each page
	Inspectors Initials Property Address Initials and Property Address are	needed on each page		spec	21013		copy of contrast
		-					rm is valid for up to five (5) years provided no material changes have been made to the structure or
	*This verification form is valid for up to five (5) years provided no material changes have been made to the structure.						n the form.
	OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155	Page 1 of 4	(IR-F	B1-18	302 (Rev. 6	01/12) Adopted by Rule 69O-170.0155 Page 2 of 4



property insurance

Wind Mitigation Discount

	de	pening Protection: What is the <u>weakest</u> form of wind borne debris prote termine the weakest form of protection for each category of opening. See sed upon the lowest protection level for ALL Glazed openings and (b) c	cond, (a) c	heck one	answer be	elow (A,	, B, C	C, N, or X)	1.	□ N. Exterior Opening Protection (unverified shutter systems with no documentation) All Glazed openings are protected wi protective coverings not meeting the requirements of Answer "A", "9", or C" or systems that appear to meet Answer "A" or "I with no documentation of compliance (Level N in the table above).
.2, or .3) as applicable.									None	N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist
Opening Protection Level Chart			Glazed Openings Non-Glazed				1	Non-Glazed Openings	None	N.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level X in the table above
		ce an "X" in each row to identify all forms of protection in use for each	Mindows				None	N.3 One or More Non-Glazed openings is classified as Level X in the table above		
		ening type. Check only one answer below (A thru X), based on the weakest on of protection (lowest row) for any of the Glazed openings and indicate	or Entry	Garage	Skylights	Glass Block	Ent Do		Vone	X. None or Some Glazed Openings One or more Glazed openings classified and Level X in the table above.
		weakest form of protection (lowest row) for Non-Glazed openings.	Doors	Duois		BIOCK][~	lois books	VOLIC	This section must be completed in full
	N/						<u> </u>			MITIGATION INSPECTIONS MUST BE CERTIFIED BY A QUALIFIED INSPECTOR.
	^						#∟			Section 627.711(2), Florida Statutes, provides a listing of individuals who may sign this form.
	В			_			₩.			Jualified Inspector Name: License or Certificate #:
	(IJ.		l †	repection Company: Phone:
	0	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance					11		L	
		Opening Protection products that appear to be A or B but are not verified					11		l	Qualified Inspector – I hold an active license as a: (check one)
	L	Other protective coverings that cannot be identified as A, B, or C					Ш		l	Home inspector licensed under Section 468.8314, Florida Statutes who has completed the statutory number of hours of hurricane mitigation
	×	No Windborne Debris Protection								training approved by the Construction Industry Licensing Board and completion of a proficiency exam.
		A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb	a for ekvlic	this only	All Glaz	ad onen	inae	are protected		Building code inspector certified under Section 468.607, Florida Statutes. One box from this
	_	a minimum, with impact resistant coverings or products listed as wind b								General, building or residential contractor itemsed under Section 493.111, Profita Statutes.
		system of the State of Florida or Miami-Dade County and meet the requ	uirements o	of one of	the follow	ing for	"Cycl	lic Pressure		Trotesional engineer necesses under Section 471.013, Protein Statutes.
		and Large Missile Impact" (Level A in the table above).								Professional architect licensed under Section 481.213, Florida Statutes. Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation.
		 Miami-Dade County PA 201, 202, and 203 								Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation verification form pursuant to Section 627.711(2), Florida Statutes.
		 Florida Building Code Testing Application Standard (TAS) 20 							-	* **
		 American Society for Testing and Materials (ASTM) E 1886; 	and ASTM	E 1996						individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed under Section 471.015, Florida Statutes, must inspect the structures personally and not through employees or other persons.
		 Southern Standards Technical Document (SSTD) 12 								Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and
		 For Skylights Only: ASTM E 1886 and ASTM E 1996 								experience to conduct a mitigation verification inspection.
urrio	ane	For Garage Doors Only: ANSI/DASMA 115								am a qualified inspector and I personally performed the inspection or (licensed
ırric	ane	 □ A.1 All Non-Glazed openings classified as A in the table above, or no Non-G □ A.2 One or More Non-Glazed openings classified as Level D in the table abore. 	mazed openi	ngs exist	d ononland	alanaiffa	d on T	Local B. C. N.		(print name)
41110	ane	X in the table above	ove, and no	Non=Giaze	a openings	ciassine	d as i	Level B, C, N,	or	contractors and professional engineers only) I had my employee () perform the inspection
urrio	ane	A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X i	in the table a	bove						(print name of inspector) and I agree to be responsible for his/her work. Inspector name/employee, signature, date is required
		B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb I			5 lb for	skylight	ts on	ılv) All Glaz		Dualified Inspector Signature; Date:
		openings are protected, at a minimum, with impact resistant coverings								Quantied inspector Signature: Date:
		in the product approval system of the State of Florida or Miami-Dade (meet the	requirem	ents of	one o	of the follow	ng	An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form
	for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):					subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the				
		 ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.) 								appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector whe certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally
		 SSTD 12 (Large Missile – 4 lb. to 8 lb.) 								performed the inspection.
asic		 For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large B.1 All Non-Glazed openings classified as A or B in the table above, or no N 								
asic		B.1 All Non-Glazed openings classified as A or B in the table above, or no N B.2 One or More Non-Glazed openings classified as Level D in the table abo				alaasifia	d on Y	Laural C. N. on		Homeowner to complete: I certify that the named Qualified Inspector or his or her employee did perform an inspection of the esidence identified on this form and that proof of identification was provided to me or my Authorized Representative.
1510		in the table above	ive, and no r	voi P Olaze	a openings	ciassine	c as i	Level C, N, or		
asic		B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the	ne table abov	re						Signature: Date:
		C. Exterior Opening Protection- Wood Structural Panels meeti plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2					s are	e covered w	th	Homeowner signature and date is preferred An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to
one		C.1 All Non-Glazed openings classified as A, B, or C in the table above, or n				-,-				obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor
one		C.2 One or More Non-Glazed openings classified as Level D in the table abo				classifie	vi se I	Level Nor X is		of the first degree. (Section 627.711(7), Florida Statutes)
		the table above	re, and no :	voir-critico	u openings	CIGISTITIC				The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature
one		C.3 One or More Non-Glazed openings is classified as Level N or X in the ta								s offering protection from hurricanes.
	Inspe	ctors InitialsProperty Address Initials and Property Address	dress are	e neede	ed on e	ach pa	age	_		inspectors Initials Property Address Initials and Property Address are needed on each page
	*This	verification form is valid for up to five (5) years provided no materi	ial changes	have be	en made	to the st	truct	ture or		This verification form is valid for up to five (5) years provided no material changes have been made to the structure or
	inacc	racies found on the form.								naccuracies found on the form. DIR-B1-1802 (Rev. 01/12) Adopted by Rule 690-170.0155 Page 4 of 4
	OIR-	31-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155				Page 3	of 4			DIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 4 of 4